

**20** bar operating pressure

RAL 9005 standard colour

## **DESCRIPTION**

Humidity indicator CHI has been designed for optical indication of dew point in compressed air system. Humidity / dew point is determined based on the colour of a silica gel, from orange (dry) to translucent (wet).

CHI can be used in variety of applications. For applications not listed please contact producer or your local distributor.


## **APPLICATIONS**


- Desiccant dryers
- General compressed air






TECHNICAL DATA									
Operating pressure	0-20 bar <sub>a</sub>					0-290 psi			
Total weight	375 g					0,83 lbs			
Adsorbent weight	75 g					0,66 lbs			
Typical installation	Head of filter housing								
Accuracy									
Air loss	Some compressed air is lost due to the operation of the indicator.								
	A	В	С	D		E	F	G	
Dimensions (mm)	81	55	80	84		M5	24	57	
Silicagel colour	Condition					Dew point			
Orange	Dry air					-25°C			
Translucent	Wet air				+15°C				







## **omega air**Air and Gas Treatment





OMEGA AIR d.o.o. Ljubljana

**T +386 (0)1 200 68 00** F +386 (0)1 200 68 50

info@omega-air.si

Cesta Dolomitskega odreda 10 SI-1000 Ljubljana, Slovenia **www.omega-air.si** 

## **Distribuidor Autorizado:**





Rua Silvio Pinto Ribeiro, 1625 Quississana, São José dos Pinhais - PR CEP: 83085-400

Fone: +55 41 3081 3050 vendas@megafilter.com.br

