

AOK 16B SERIES AUTOMATIC MECHANICAL CONDENSATE DRAIN

16 bar operating pressure

1/2" connections

1,5 to **65** °C operating temperature range


DESCRIPTION

AOK 16B is designed for fully automatic discharging of condensate or any other non aggressive fluid from compressed air system. For any other technical gas please contact producer or your local distributor. AOK 16B is easy to install inside to the filter housing.

AOK 16B can be used in a variety of applications. For applications not listed please contact producer or your local distributor.



TECHNICAL DATA	AOK 16B
Operating temp. range	1,5 - 65 °C (35-149 °F)
Operating pressure	16 bar (232 psi)
Mass	0,04 kg
Connection	G 1/2"
Outlet connection	ø8
Dimensions H × D	90 × ø38,5 mm
Medium	Condensate (air, water, oil)



APPLICATIONS

- Cyclone condensate separator
- Air filter

omega airAir and Gas Treatment





OMEGA AIR d.o.o. Ljubljana

T +386 (0)1 200 68 00 F +386 (0)1 200 68 50

info@omega-air.si

Cesta Dolomitskega odreda 10 SI-1000 Ljubljana, Slovenia **www.omega-air.si**

Distribuidor Autorizado:





Rua Silvio Pinto Ribeiro, 1625 Quississana, São José dos Pinhais - PR CEP: 83085-400

Fone: +55 41 3081 3050 vendas@megafilter.com.br

